





General:	Assembled by A&I Manufacturing, Inc. Environmentally safe.
Fabric:	Translucent or Room Darkening spun lace, non woven fabric. 100% Polyester.
Head Rail:	1 1/2" High x 1 3/4" Deep extruded aluminum, with PVC end caps. Depth with installation bracket is 2".
Bottom Rail:	1/2" High x 1 5/8" deep extruded aluminum with PVC end caps.
Cordless Modules:	Cordless modules are constructed with clear PVC body. Lift cord is wound inside the module. Steel spring provides tension to pull the shade up. A steel d-rod link all modules together inside the head rail.
Lift Cord:	Shall be braided polyester and of sufficient length to control the raising and lowering of the shade. Outside diameter is 0.9mm.
Weights:	100% Steel, Zinc plated with double sided tape.
Handle:	100% PVC
Installation Brackets:	Constructed of cold rolled steel. Zinc plated. Hex head screws are included. Intermediate brackets spaced no wider than 36" apart.
Sizes:	Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal shades will have 1/2" deducted at the factory from width. <i>See Product Limits.</i>

Product Limits

Controls (Manual)	Min. Width	Max. Width	Min. Drop	Max. Drop
Cordless	12"	96"	10"	*84"

Maximum Sq. Footage *48 Sq. Ft. Under Warranty

* Exceptions Available Upon Request

		WARNING Window Blind Cord Can STRANGLE Your Child. Keep cords out of children's reach. Shorten cords to prevent reach. Move crib and furniture away – Children can climb furniture to reach cords.
		ADVERTENCIA La cuerda de la persiana puede ESTRANGULAR a su niño. Mantenga las cuerdas fuera del alcance de los niños. Acorte las cuerdas para evitar el al Mueva la cuna y los muebles – Los niños pueden subir los muebles para alcanzar las c

