



General:	Assembled by A&I Manufacturing, Inc. Environmentally safe.
Fabric:	Translucent or Room Darkening spun lace, non woven fabric. 100% Polyester
Top Head Rail:	1 1/2" high x 1 3/4" deep extruded aluminum with PVC end caps. Depth with installation bracket is 2".
Mid Head Rail:	3/4" high x 1 5/8" deep extruded aluminum with PVC end caps.
Bottom Rail:	1/2" high x 1 5/8" deep extruded aluminum with PVC end caps.
Cord Lock:	Cord lock shall be secured to the head rail channel. Lock body shall be constructed of clear polycarbonate,. Floating gear and pins locks shall e made of brass. Cord lock to be of crash-proof design.
Cord Cleat:	Cleat is made of clear 100% PVC.
Lift Cord:	Shall be braided polyester and of sufficient length to control the raising and lowering of the shade. Outside diameter is 0.9mm.
Pull Cord:	Shall braided polyester and of sufficient length to control raising and lowering of shade. Outside diameter is 1.8mm.
Tassel:	100% PVC. Shall comply with all safety requirements.
Stop Ball:	100% PVC. Shall comply with all safety requirements.
Installation Brackets:	Constructed of cold rolled steel. Zinc plated. Intermediate brackets spaced no wider than 36" apart.
Sizes:	Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal shades will have 1/2" deducted at the factory from width. <i>See Product Limits.</i>

Product Limits

Controls (Manual)	Min. Width	Max. Width	Min. Drop	Max. Drop
Standard	12"	72"	10"	*72"

Maximum Sq. Footage *36 Sq. Ft. Under Warranty

* Exceptions Available Upon Request



