

1.1 HORIZONTAL BLINDS, 2 INCH

A. Horizontal Blinds Construction General:

1. Headrail: .024 inch steel. Treated to resist corrosion. Baked-on paint, color coordinated to slats.
2. Bottom Rail: Steel, thickness varies with product type. Treated to resist corrosion. Baked-on paint, color coordinated to slats.
3. Tilter: Worm gear construction, enclosed in housing of engineering polymer; gear and shaft of engineering polymer with slip clutch mechanism. May be positioned at right or left with or without cord lock.
4. Tilt Rod: Solid steel with corrosion resistant finish.
5. Tilt Wands: Extruded, clear solid acrylic wand.
6. Cord lock: Snap-In-Design and incorporates stainless steel wear guard over which cords pass and a floating type locking pin. Locking pin shall be free of abrasive teeth and offer minimum wear to the cord
7. Lift Cords: Two-ply polyester cord filler and braided polyester jacket.
8. Braided Ladders: 100 percent polyester yarn, color coordinated with the slats.
9. Installation Brackets: .042 inch steel box brackets. Blinds over 48 inches shall have intermediate supports.
10. Tassel: Break away safety tassel complies with all safety requirements
11. Can be motorized for tilt model only.

B. Aluminum Standard Horizontal Blinds 2 inch (51 mm):

1. Slats:
 - a. Aluminum Heat Treated and Tempered, 2 inches wide by .008 inch thick.
2. Maximum Width: 122 inches (3048 mm).
3. Maximum Drop: 120 inches (3099 mm).
4. Slat Spacing: 44 mm spacing with 7 slats per foot of drop.
5. Control Electric: Coordinate with Motors and Controls specified in Section 12 25 13 - Motorized Drapery Rods.

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a.

Tilt Only-Center of Headrail
- b. Split control LR.
- c. Split control RL.
- d. Same side control LR.
- e. Same side control RL.
6. Control Manual:

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a.

Tilt Only-Center of Headrail
- b. Split control LR.
- c. Split control RL.
- d. Same side control RR.
- e. Same side control LL.
7. Mounting:

**** NOTE TO SPECIFIER ** Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a.

Inside mount.

- b. Outside mount.
- 8. Head Rail: 2 inch by 2 inch.
- 9. Bottom Rail: Enclosed steel, color coordinated.

**** NOTE TO SPECIFIER ** Select one of the following two valance options as required. Delete the one not required.**

- 10. Valance: Single Slat with clips to mount.
- 11. Valance: Double Slat with clips to mount.

**** NOTE TO SPECIFIER ** Available in 19 colors.**

- 12. Slat color as selected by Architect from fabricator's available selections.
- 13. Decorative Tape: 1-1/2 inch wide woven, 100 percent cotton cloth tape ladder, color coordinated with the slats.
- C. Designer Vinyl Horizontal Blinds 2 inch (51 mm):
 - 1. Slats:
 - a. Polymer PVC, 2 inches wide.
 - 2. Maximum Width: 120 inches (3099 mm).
 - 3. Maximum Drop: 114 inches (2895 mm).
 - 4. Slat Spacing: 44 mm spacing with 7 slats per foot of drop.
 - 5. Control Electric: Coordinate with Motors and Controls specified in Section 12 25 13 - Motorized Drapery Rods.

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. Tilt Only-Center of Headrail
- b. Split control LR.
- c. Split control RL.
- d. Same side control LR.
- e. Same side control RL.
- 6. Control Manual:

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. Tilt Only-Center of Headrail
- b. Split control LR.
- c. Split control RL.
- d. Same side control RR.
- e. Same side control LL.
- 7. Mounting:

**** NOTE TO SPECIFIER ** Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. Inside mount.
- b. Outside mount.
- 8. Head Rail: 2 inch by 2 inch.
- 9. Bottom Rail: Enclosed steel, color coordinated.

**** NOTE TO SPECIFIER ** Select one of the following two valance options as required. Delete the one not required.**

10. _____
Valance: Single Slat with clips to mount.
11. _____
Valance: Double Slat with clips to mount.

**** NOTE TO SPECIFIER ** Available in 16 colors.**

12. _____
Slat color as selected by Architect from fabricator's available selections.
13. _____
Decorative Tape: 1-1/2 inch wide woven, 100 percent cotton cloth tape ladder, color coordinated with the slats.
- D. Olympic Ridge (Faux) Horizontal Blinds 2 inch (51 mm):
 1. Slats:
 - a. Faux (Foam), 2 inches wide by 1/8 inch thick.
 2. Maximum Width: 108 inches (2743 mm).
 3. Maximum Drop: 108 inches (2743 mm).
 4. Slat Spacing: 44 mm spacing with 7 slats per foot of drop.
 5. Control Electric: Coordinate with Motors and Controls specified in Section 12 25 13 - Motorized Drapery Rods.

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. _____
Tilt Only-Center of Headrail
- b. _____
Split control LR.
- c. _____
Split control RL.
- d. _____
Same side control LR.
- e. _____
Same side control RL.
6. Control Manual:

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. _____
Tilt Only-Center of Headrail
- b. _____
Split control LR.
- c. _____
Split control RL.
- d. _____
Same side control RR.
- e. _____
Same side control LL.
7. Mounting:

**** NOTE TO SPECIFIER ** Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. _____
Inside mount.
- b. _____
Outside mount.
8. Head Rail: 2 inch by 2 inch.
9. Bottom Rail: Trapezoid faux wood, color coordinated.
10. Valance: Royal.

**** NOTE TO SPECIFIER ** Available in 20 colors.**

11. _____
Slat color as selected by Architect from fabricator's available selections.
12. _____
Decorative Tape: 1-1/2 inch wide woven, 100 percent cotton cloth tape ladder, color coordinated with the slats.
- E. Olympic Ridge (Faux) Horizontal Blinds 2-1/2 inch (63 mm):
 1. Slats:

- a. Faux (Foam), 2-1/2 inches wide by 1/8 inch thick.
2. Maximum Width: 108 inches (2743 mm).
3. Maximum Drop: 108 inches (2743 mm).
4. Slat Spacing: 44 mm spacing with 7 slats per foot of drop.
5. Control Electric: Coordinate with Motors and Controls specified in Section 12 25 13 - Motorized Drapery Rods.

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. Tilt Only-Center of Headrail
- b. Split control LR.
- c. Split control RL.
- d. Same side control LR.
- e. Same side control RL.
6. Control Manual:

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. Tilt Only-Center of Headrail
- b. Split control LR.
- c. Split control RL.
- d. Same side control LR.
- e. Same side control RL.
7. Mounting:

**** NOTE TO SPECIFIER ** Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. Inside mount.
- b. Outside mount.
8. Head Rail: 2 inch by 2 inch.
9. Bottom Rail: Trapezoid faux wood, color coordinated.
10. Valance: Royal.

**** NOTE TO SPECIFIER ** Available in 5 colors.**

11. Slat color as selected by Architect from fabricator's available selections.
- F. Summit Woods (Basswood) Horizontal Blinds 2 inch (51 mm):
1. Slats:
 - a. Basswood, 2 inches wide by 1/8 inch thick.
 2. Maximum Width: 96 inches (2438 mm).
 3. Maximum Drop: 120 inches (3048 mm).
 4. Slat Spacing: 44 mm spacing with 7 slats per foot of drop.
 5. Control Electric: Coordinate with Motors and Controls specified in Section 12 25 13 - Motorized Drapery Rods.

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. Tilt Only-Center of Headrail
- b. Split control LR.
- c. Split control RL.
- d. Same side control LR.

- e. Same side control RL.
6. Control Manual:

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. Tilt Only-Center of Headrail
 - b. Split control LR.
 - c. Split control RL.
 - d. Same side control LR.
 - e. Same side control RL.
7. Mounting:

**** NOTE TO SPECIFIER ** Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. Inside mount.
 - b. Outside mount.
8. Head Rail: 2 inch by 2 inch.
9. Bottom Rail: Trapezoid basswood, color coordinated.
10. Valance: Royal.

**** NOTE TO SPECIFIER ** Available in 16 colors.**

11. Slat color as selected by Architect from fabricator's available selections.
12. Decorative Tape: 1-1/2 inch wide woven, 100 percent cotton cloth tape ladder, color coordinated with the slats.

**** NOTE TO SPECIFIER ** Select the vertical blinds required from the following paragraphs as required and delete those not required. Note that the maximum size width and drop noted apply to residential blinds with a lifetime warranty. Custom widths and drops are available upon request. Vertical blinds may be used with motors and controls specified in Section 12 25 13 - Motorized Drapery Rods. Contact the manufacturer for additional information.**