

1.1 CELLULAR SHADES

A. Single Cell Light Filtering Shade System:

1. Material: High Quality Spun lace non-woven 100 percent polyester fabric.

**** NOTE TO SPECIFIER ** Select the thickness required. Delete the one not required.**

- a. _____
Single Cell 3/8 inch.
- b. _____
Single Cell 3/4 inch.

**** NOTE TO SPECIFIER ** Select the following option if required. Delete if not required.**

- c. _____
Treated to meet NFPA 701 fire retardant standards.

**** NOTE TO SPECIFIER ** Available in 30 colors.**

- d. _____
Color as selected by Architect from fabricator's available selections.
2. Maximum Width: 84 inches (2134 mm).
3. Maximum Drop: 82 inches (2083 mm).

**** NOTE TO SPECIFIER ** Select Control Device Type. Delete those not required. Coordinate maximum width with control type specified.**

4. _____
Control Manual:

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. _____
Lift Ease.
- b. _____
Cordless.
- c. _____
Standard control.
- d. _____
Standard TD/BU.
- e. _____
Cordless TD/BU.
5. Control Electric: Coordinate with Motors and Controls specified in Section 12 25 13 - Motorized Drapery Rods.

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. _____
Lift Ease.
- b. _____
Cordless.
- c. _____
Standard control.
- d. _____
Standard TD/BU.
- e. _____
Cordless TD/BU.
6. Mounting:

**** NOTE TO SPECIFIER ** Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 3/8 inch deducted at the factory from width.**

- a. _____
Inside mount.
- b. _____
Outside mount.
7. Head Rail:

**** NOTE TO SPECIFIER ** Select one of the following options as required. Delete the one not required.**

- a. _____
Standard head rail.
 - b. _____
Two on one head rail.
- B. Double Cell Light Filtering Shade System:
- 1. Material: High Quality Spun lace non-woven 100 percent polyester fabric.
 - a. _____
Double Cell 7/16 inch.

**** NOTE TO SPECIFIER ** Select the following option if required. Delete if not required.**

- b. _____
Treated to meet NFPA 701 fire retardant standards.

**** NOTE TO SPECIFIER ** Available in 30 colors.**

- c. _____
Color as selected by Architect from fabricator's available selections.
- 2. _____
Maximum Width: 84 inches (2134 mm).
 - 3. _____
Maximum Drop: 82 inches (2083 mm).

**** NOTE TO SPECIFIER ** Select Control Device Type. Delete those not required. Coordinate maximum width with control type specified.**

- 4. _____
Control Manual:

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. _____
Lift Ease.
 - b. _____
Cordless.
 - c. _____
Standard control.
 - d. _____
Standard TD/BU.
 - e. _____
Cordless TD/BU.
- 5. Control Electric: Coordinate with Motors and Controls specified in Section 12 25 13 - Motorized Drapery Rods.

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. _____
Lift Ease.
 - b. _____
Cordless.
 - c. _____
Standard control.
 - d. _____
Standard TD/BU.
 - e. _____
Cordless TD/BU.
- 6. Mounting:

**** NOTE TO SPECIFIER ** Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 3/8 inch deducted at the factory from width.**

- a. _____
Inside mount.
 - b. _____
Outside mount.
- 7. Head Rail:

**** NOTE TO SPECIFIER ** Select one of the following options as required. Delete the one not required.**

- a. _____
Standard head rail.
 - b. _____
Two on one head rail.
- C. Single Cell Darkening Shade System:
- 1. Material: High Quality Spun lace non-woven 100 percent polyester fabric.

**** NOTE TO SPECIFIER ** Select the thickness required. Delete the one not required.**

- a. _____
Single Cell 3/8 inch.
- b. _____
Single Cell 3/4 inch.

**** NOTE TO SPECIFIER ** Select the following option if required. Delete if not required.**

- c. _____
Treated to meet NFPA 701 fire retardant standards.

**** NOTE TO SPECIFIER ** Available in 16 colors.**

- d. _____
Color as selected by Architect from fabricator's available selections.
- 2. Maximum Width: 84 inches (2134 mm).
 - 3. Maximum Drop: 82 inches (2083 mm).

**** NOTE TO SPECIFIER ** Select Control Device Type. Delete those not required. Coordinate maximum width with control type specified.**

- 4. _____
Control Manual:

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. _____
Lift Ease.
 - b. _____
Cordless.
 - c. _____
Standard control.
 - d. _____
Standard TD/BU.
 - e. _____
Cordless TD/BU.
- 5. Control Electric: Coordinate with Motors and Controls specified in Section 12 25 13 - Motorized Drapery Rods.

**** NOTE TO SPECIFIER ** Select Control required. Delete those not required.**

- a. _____
Lift Ease.
 - b. _____
Cordless.
 - c. _____
Standard control.
 - d. _____
Standard TD/BU.
 - e. _____
Cordless TD/BU.
- 6. Mounting:

**** NOTE TO SPECIFIER ** Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 3/8 inch deducted at the factory from width.**

- a. _____
 - b. Inside mount.
7. Head Rail:

**** NOTE TO SPECIFIER ** Select one of the following options as required. Delete the one not required.**

- a. _____
 - b. Standard head rail.
- Two on one head rail.

**** NOTE TO SPECIFIER ** Select the roller shades required from the following paragraphs as required and delete those not required. Note that the maximum size width and drop noted apply to residential blinds with a lifetime warranty. Custom widths and drops are available upon request. Roller shades may be used with motors and controls specified in Section 12 25 13 - Motorized Drapery Rods. Contact the manufacturer for additional information.**