

1.1

---

MINI BLINDS

- A. Mini Blind Construction General:
1. Headrail: .024 inch steel. Treated to resist corrosion. Baked-on paint, color coordinated to slats.
  2. Bottom Rail: .024 inch steel. Treated to resist corrosion. Baked-on paint, color coordinated to slats.
  3. Tilter: Worm gear construction, enclosed in housing of engineering polymer; gear and shaft of engineering polymer with slip clutch mechanism. May be positioned at right or left with or without cord lock.
  4. Tilt Rod: Solid steel with corrosion resistant finish.
  5. Tilt Wands: Extruded, clear solid acrylic wand.
  6. Cord lock: Snap-In-Design and incorporates stainless steel wear guard over which cords pass and a floating type locking pin. Locking pin shall be free of abrasive teeth and offer minimum wear to the cord
  7. Lift Cords: Two-ply polyester cord filler and braided polyester jacket.
  8. Braided Ladders: 100 percent polyester yarn, color coordinated with the slats.
  9. Installation Brackets: .042 inch steel box brackets. Blinds over 48 inches shall have intermediate supports.
  10. Tassel: Break away safety tassel complies with all safety requirements.
- B. Mini Economy Mini-Blinds 1 inch (25 mm) Horizontal Blind System:
1. Slats:

---

**\*\* NOTE TO SPECIFIER \*\* Select slat thickness required. Delete the one not required.**

- a. 

---

Aluminum Heat Treated and Tempered, 1 inch wide by .006 inch thick.
  - b. Aluminum Heat Treated and Tempered, 1 inch wide by .008 inch thick.
2. Maximum Width: 132 inches (3353 mm).

---

**\*\* NOTE TO SPECIFIER \*\* Longer lengths available, out of warranty contact manufacturer for additional information.**

3. 

---

Maximum Drop: 126 inches (3200 mm).
4. Slat Spacing: 22.5 mm spacing with approximately 13 slats per foot of drop.
5. Mounting:

---

**\*\* NOTE TO SPECIFIER \*\* Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. 

---

Inside mount.
  - b. Outside mount.
6. Control Manual:

---

**\*\* NOTE TO SPECIFIER \*\* Select Control Device Type. Delete those not required.**

- a. 

---

Tilt Only-Center of Headrail
- b. Split control LR.

- c. Split control RL.
- d. Same side control RR.
- e. Same side control LL.
- 7. Head Rail: Standard duty 1 inch by 1 inch.
- 8. Bottom Rail: C-Shape.

---

**\*\* NOTE TO SPECIFIER \*\* Select optional valance if required. Delete if not required.**

- 9. Valance: Double Slat with clips to mount.

---

**\*\* NOTE TO SPECIFIER \*\* Available in 7 colors.**

- 10. Slat color as selected by Architect from fabricator's available selections.
- C. Mini Deluxe Mini-Blinds 1 inch (25 mm) Horizontal Blind System:
  - 1. Slats:

---

**\*\* NOTE TO SPECIFIER \*\* Select slat thickness required. Delete the one not required.**

- a. Aluminum Heat Treated and Tempered, 1 inch wide by .006 inch thick.
- b. Aluminum Heat Treated and Tempered, 1 inch wide by .008 inch thick.
- 2. Maximum Width: 132 inches (3353 mm).

---

**\*\* NOTE TO SPECIFIER \*\* Longer lengths available, out of warranty contact manufacturer for additional information.**

- 3. Maximum Drop: 126 inches (3200 mm).
- 4. Slat Spacing: 21.5 mm spacing with approximately 14 slats per foot of drop.
- 5. Mounting:

---

**\*\* NOTE TO SPECIFIER \*\* Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. Inside mount.
- b. Outside mount.
- 6. Control Manual:

---

**\*\* NOTE TO SPECIFIER \*\* Select Control Device Type. Delete those not required.**

- a. Tilt Only-Center of Headrail
- b. Split control LR.
- c. Split control RL.
- d. Same side control RR.
- e. Same side control LL.
- 7. Head Rail: Standard duty 1 inch by 1 inch.
- 8. Bottom Rail: C-Shape.

---

**\*\* NOTE TO SPECIFIER \*\* Select optional valance if required. Delete if not required.**

- 9. Valance: Double Slat with clips to mount.

---

**\*\* NOTE TO SPECIFIER \*\* Available in 7 colors.**

10. \_\_\_\_\_  
Slat color as selected by Architect from fabricator's available selections.
- D. Mini Privacy Mini-Blinds 1 inch (25 mm) Horizontal Blind System:
1. Slats:

---

**\*\* NOTE TO SPECIFIER \*\* Select slat thickness required. Delete the one not required.**

- a. \_\_\_\_\_  
Aluminum Heat Treated and Tempered, 1 inch wide by .006 inch thick.
- b. Aluminum Heat Treated and Tempered, 1 inch wide by .008 inch thick.
2. Maximum Width: 132 inches (3353 mm).

---

**\*\* NOTE TO SPECIFIER \*\* Longer lengths available, out of warranty contact manufacturer for additional information.**

3. \_\_\_\_\_  
Maximum Drop: 126 inches (3200 mm).
4. Slat Spacing: 18.5 mm spacing with approximately 17 slats per foot of drop.
5. Mounting:

---

**\*\* NOTE TO SPECIFIER \*\* Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. \_\_\_\_\_  
Inside mount.
- b. Outside mount.
6. Control Manual:

---

**\*\* NOTE TO SPECIFIER \*\* Select Control Device Type. Delete those not required.**

- a. \_\_\_\_\_  
Tilt Only-Center of Headrail
- b. Split control LR.
- c. Split control RL.
- d. Same side control RR.
- e. Same side control LL.
7. Head Rail: Standard duty 1 inch by 1 inch.
8. Bottom Rail: C-Shape.

---

**\*\* NOTE TO SPECIFIER \*\* Select optional valance if required. Delete if not required.**

9. \_\_\_\_\_  
Valance: Double Slat with clips to mount.

---

**\*\* NOTE TO SPECIFIER \*\* Available in 7 colors.**

10. \_\_\_\_\_  
Slat color as selected by Architect from fabricator's available selections.
- E. Custom Economy Series Mini-Blinds 1 inch (25 mm) Horizontal Blind System:
1. Slats:

---

**\*\* NOTE TO SPECIFIER \*\* Select slat thickness required. Delete the one not required.**

- a. \_\_\_\_\_  
Aluminum Heat Treated and Tempered, 1 inch (25 mm) wide by .006 inch thick.
  - b. \_\_\_\_\_  
Premium Aluminum Heat Treated and Tempered, 1 inch (25 mm) wide by .008 inch thick.
2. \_\_\_\_\_  
Maximum Width: 132 inches (3353 mm).

**\*\* NOTE TO SPECIFIER \*\* Longer lengths available, out of warranty contact manufacturer for additional information.**

3. \_\_\_\_\_  
Maximum Drop: 126 inches (3200 mm).
4. \_\_\_\_\_  
Slat Spacing: 22.5 mm spacing with approximately 13 slats per foot of drop.
5. \_\_\_\_\_  
Mounting:

**\*\* NOTE TO SPECIFIER \*\* Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. \_\_\_\_\_  
Inside mount.
  - b. \_\_\_\_\_  
Outside mount.
6. \_\_\_\_\_  
Control Manual:

**\*\* NOTE TO SPECIFIER \*\* Select Control Device Type. Delete those not required.**

- a. \_\_\_\_\_  
Tilt Only-Center of Headrail
  - b. \_\_\_\_\_  
Split control LR.
  - c. \_\_\_\_\_  
Split control RL.
  - d. \_\_\_\_\_  
Same side control RR.
  - e. \_\_\_\_\_  
Same side control LL.
7. \_\_\_\_\_  
Head Rail: Standard duty 1.5 inch by 1 inch.
8. \_\_\_\_\_  
Bottom Rail: Standard duty sculpted.

**\*\* NOTE TO SPECIFIER \*\* Select optional valance if required. Delete if not required.**

9. \_\_\_\_\_  
Valance: Double Slat with clips to mount.

**\*\* NOTE TO SPECIFIER \*\* Available in 42 colors with .006 inch slats and 19 colors for .008 inch slats.**

10. \_\_\_\_\_  
Slat color as selected by Architect from fabricator's available selections.
- F. \_\_\_\_\_  
Custom Deluxe Mini-Blinds 1 inch (25 mm) Horizontal Blind System:
1. \_\_\_\_\_  
Slats:

**\*\* NOTE TO SPECIFIER \*\* Select slat thickness required. Delete the one not required.**

- a. \_\_\_\_\_  
Aluminum Heat Treated and Tempered, 1 inch (25 mm) wide by .006 inch thick.
  - b. \_\_\_\_\_  
Premium Aluminum Heat Treated and Tempered, 1 inch (25 mm) wide by .008 inch thick.
2. \_\_\_\_\_  
Maximum Width: 132 inches (3353 mm).

**\*\* NOTE TO SPECIFIER \*\* Longer lengths available, out of warranty contact manufacturer**

for additional information.

3. \_\_\_\_\_  
Maximum Drop: 126 inches (3200 mm).
4. Slat Spacing: 21.5 mm spacing with approximately 14 slats per foot of drop.
5. Mounting:

**\*\* NOTE TO SPECIFIER \*\* Select one of the following two mounting options as required. Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. \_\_\_\_\_  
Inside mount.
- b. \_\_\_\_\_  
Outside mount.
6. Control Manual:

**\*\* NOTE TO SPECIFIER \*\* Select Control Device Type. Delete those not required.**

- a. \_\_\_\_\_  
Tilt Only-Center of Headrail
- b. \_\_\_\_\_  
Split control LR.
- c. \_\_\_\_\_  
Split control RL.
- d. \_\_\_\_\_  
Same side control RR.
- e. \_\_\_\_\_  
Same side control LL.
7. Head Rail: Standard duty 1.5 inch by 1 inch.
8. Bottom Rail: Standard duty sculpted.

**\*\* NOTE TO SPECIFIER \*\* Select optional valance if required. Delete if not required.**

9. \_\_\_\_\_  
Valance: Double Slat with clips to mount.

**\*\* NOTE TO SPECIFIER \*\* Available in 42 colors with .006 inch slats and 19 colors for .008 inch slats.**

10. \_\_\_\_\_  
Slat color as selected by Architect from fabricator's available selections.
- G. Custom Privacy Mini-Blinds 1 inch (25 mm) Horizontal Blind System:
  1. Slats:

**\*\* NOTE TO SPECIFIER \*\* Select slat thickness required. Delete the one not required.**

- a. \_\_\_\_\_  
Aluminum Heat Treated and Tempered, 1 inch (25 mm) wide by .006 inch thick.
- b. \_\_\_\_\_  
Aluminum Heat Treated and Tempered, 1 inch (25 mm) wide by .008 inch thick.
2. Maximum Width: 132 inches (3353 mm).

**\*\* NOTE TO SPECIFIER \*\* Longer lengths available, out of warranty contact manufacturer for additional information.**

3. \_\_\_\_\_  
Maximum Drop: 126 inches (3200 mm).
4. Slat Spacing: 18.5 mm spacing with approximately 17 slats per foot of drop.
5. Mounting:

**\*\* NOTE TO SPECIFIER \*\* Select one of the following two mounting options as required.**

**Delete the one not required. Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2 inch deducted at the factory from width.**

- a. \_\_\_\_\_  
Inside mount.
  - b. \_\_\_\_\_  
Outside mount.
6. Control Manual:

---

**\*\* NOTE TO SPECIFIER \*\* Select Control Device Type. Delete those not required.**

- a. \_\_\_\_\_  
Tilt Only-Center of Headrail
  - b. \_\_\_\_\_  
Split control RR.
  - c. \_\_\_\_\_  
Split control LL.
  - d. \_\_\_\_\_  
Same side control LR.
  - e. \_\_\_\_\_  
Same side control RL.
7. Head Rail: Standard duty 1.5 inches by 1 inch.
8. Bottom Rail: Sculpted.

---

**\*\* NOTE TO SPECIFIER \*\* Select optional valance if required. Delete if not required.**

9. \_\_\_\_\_  
Valance: Double Slat with clips to mount.

---

**\*\* NOTE TO SPECIFIER \*\* Available in 42 colors with .006 inch slats and 19 colors for .008 inch slats.**